



PCB terminal block — TL series (Wire Protector)— TL226V



PCB Layout

■ 图示(Pic. shown) : TL226V-04P-G12S

General.	PCB terminal block	Rated : 320V, 24A , 2.5mm ²
	Single row , 5.00mm pitch , 02-24 Pole	
	Connection angle: 180°(wire-to-board)	
	Screw clamp unit: M2.5, 0.4Nm Max	

认证 (Approval) : 

■ 技术参数Technical Data		UL standard			IEC standard		
UL应用组别(UL Application group)		UL Application group			IEC过电压别/污染等级(IEC overvoltage category /pollution degree)		
IEC过电压别/污染等级(IEC overvoltage category /pollution degree)							
		B	C	D	III / 3	III / 2	II / 2
额定电压(Rated voltage)		300V	--	300V	--	320V	--
额定电流(Rated current)		16A	--	10A	--	24A	--
额定连接容量(Rated connection capacity)		12-30AWG Sol&Str			0.2-2.5mm²		
绝缘材料(Insulation Material)				PA66 UL94 V-0			
电流承载部件材料和镀层(Material & Plating of Current carrier)				Copper alloy , Tin plated			
接线弹片材料(Material of Clamp spring)				--			
绝缘电阻(Insulation Resistance)				500MΩ or more at DC500V			
耐电压(1分钟)(Withstanding Voltage/1Min)				2200V			
额定冲击电压(Rated surge voltage)				--			
接线螺丝(Wire clamp unit Screw) , 最大扭矩(torque Max.)				M2.5 , 0.4Nm Max			
固定螺丝(Mounting Screw) , 扭矩(torque)				--			
剥线长度(Wire stripping length)				6.1mm			
使用温度(Operating temperature)				-40℃ up to +120℃			
焊接方式(Soldering recommend)		Wave soldering ,260℃ 5S Max (Single Wave) , 260℃ 10S Max(Double Wave)					

■ 订购方式(How to order)

TL	2	26	V	XXXX	XXP	G12	S
Series No. 系列号	Pitch间距 2=5.00mm	Differentiate Number 区分号	Connection angle 角度 V=180° wire-to-board	Special code 特编号 XXXX=custom-made blank=standard	No. of Poles 极数 02-24P	Color 颜色 Green: G12	Screw Type 螺丝S=Slot C=Cross

Web:www.china-tianli.com TEL:+86-574-6347-9600,6389-6436

Mail : sale@china-tianli.cn

地址:中国浙江省宁波杭州湾新区庵东工业园区纬三路138号

ADD : 138 , Weisan Rd., Andong Development Zone, Hangzhou Bay Area, Ningbo, Zhejiang, China