




Fuse Terminal Block — TLF series — TLF-100-01P



■ 图示(Pic. shown) : TLF-100-01P-M19S

General.	Fuse Terminal Block	Rated : 300V, 13A , 14AWG
	Single row , 01 Pole	
	Wire-to-Wire Connection	
	Screw clamp unit: M3, 0.5N.m	

认证 (Approval) :



■ 技术参数 Technical Data	UL standard			IEC standard		
UL应用组别(UL Application group)	UL Application group			IEC过电压别/污染等级(IEC overvoltage category /pollution degree)		
IEC过电压别/污染等级(IEC overvoltage category /pollution degree)	B	C	D	III / 3	III / 2	II / 2
额定电压(Rated voltage)	300V	--	300V	--	--	--
额定电流(Rated current)	13A	--	10A	--	--	--
额定连接容量(Rated connection capacity)	20AWG~14AWG			--		
刚性导线横截面 (AWG) (Conductor cross section,solid)	20~14					
柔性导线横截面 (AWG) (Conductor cross section,stranded)	20~14					
刚性导线横截面 (mm2) (Conductor cross section,rigid)	--					
柔性导线横截面 (mm2) (Conductor cross section,flexible)	--					
绝缘材料(Insulation Material)	PA66 UL94 V-0					
绝缘材料组别(Material group)	/					
电流承载部件材料和镀层(Material & Plating of Current carrier)	Copper alloy , Ni plated					
接线弹片材料(Material of Clamp spring)	--					
耐电压(1分钟)(Withstanding Voltage/1Min)	2000V					
额定冲击电压(Rated surge voltage)	--					
接线螺丝(Wire clamp unit Screw) , 最大扭矩(torque Max.)	M3, 0.5N.m					
固定螺丝(Mounting Screw) , 扭矩(torque)	--					
剥线长度(Wire stripping length)	6-7mm					
使用温度(Operating temperature)	-40°C up to +105°C					
存储温度(Storage temperature)	-40°C up to +70°C					
存储相对湿度(Storage relative humidity)	≤70%					
焊接方式(Soldering recommend)	--					

■ 订购方式(How to order)

TLF	—	100	—	XXXX	—	01P	—	X	—	X
Series No. 系列号		Differentiate Number 区分号		Special code 特编号 XXXX=custom-made blank=standard		No. of Poles 极数 01P		Color 颜色 Grey:M19		Screw Type 螺丝S=Slot C=Cross