



Fuse Terminal Block — TLF series — TLF-100



■ 图示(Pic. shown) : TLF-100-05P-M19S

General. Fuse Terminal Block Rated : 300V,30A , 10AWG
Single row , 10.00mm pitch , 02-06 Pole
Wire-to-Wire Connection
Screw clamp unit: M3, 0.5N.m

认证 (Approval) :



■ 技术参数Technical Data		UL standard			IEC standard		
UL应用组别(UL Application group)		UL Application group			IEC过电压别/污染等级(IEC overvoltage category /pollution degree)		
IEC过电压别/污染等级(IEC overvoltage category /pollution degree)		B	C	D	III / 3	III / 2	II / 2
额定电压(Rated voltage)		300V	--	300V	--	--	--
额定电流(Rated current)		Terminal :30A Fuse: 13A	--	10A	--	--	--
额定连接容量(Rated connection capacity)		Terminal Block: 18AWG~10AWG			--		
刚性导线横截面 (AWG) (Conductor cross section,solid)				Terminal Block: 18~10 / Fuse Holder: 20~14			
柔性导线横截面 (AWG) (Conductor cross section,stranded)				Terminal Block: 18~10 / Fuse Holder: 20~14			
刚性导线横截面 (mm2) (Conductor cross section,rigid)				--			
柔性导线横截面 (mm2) (Conductor cross section,flexible)				--			
绝缘材料(Insulation Material)				PA66 UL94 V-0			
绝缘材料组别(Material group)				/			
电流承载部件材料和镀层(Material & Plating of Current carrier)				Copper alloy , Ni plated			
接线弹片材料(Material of Clamp spring)				--			
耐电压(1分钟)(Withstanding Voltage/1Min)				Terminal Block: 2500V / Fuse Holder: 2000V			
额定冲击电压(Rated surge voltage)				--			
接线螺丝(Wire clamp unit Screw) , 最大扭矩(torque Max.)				M3, 0.5N.m			
固定螺丝(Mounting Screw) , 扭矩(torque)				--			
剥线长度(Wire stripping length)				6-7mm			
使用温度(Operating temperature)				-40℃ up to +105℃			
存储温度(Storage temperature)				-40℃ up to +70℃			
存储相对湿度(Storage relative humidity)				≤70%			
焊接方式(Soldering recommend)		--					

■ 订购方式(How to order)

